คุณภาพคุ้มค่า ตอบทุกความต้องการ

IP High Speed, 2.0MP 20X optical zoom

N-IP7235

120M IR Intelligent High Speed IP Dome

Main Features

1) Intelligent high speed IP camera, with 10pcs of Taiwan imported LED, 120M IR Distance,
2) Adopt new aluminum alloy construction, which ensures convenient installation as well as stable performance
3) Precise subdivision technology, can accurately capture stable image of moving acts under zoom condition
4) Horizontal overturn scan: 360°, Vertical revolving range: 90°/180°(auto flip)
5) High Speed: Pan speed: 180°/s, Tilt speed: 80°/s
6) 128 Preset Positions, 8 tours
7) PELCO-D, PELCO-P automatic identification, Baud Rate: 2400/4800/9600/19200
8) with wall mount bracket

2.0MP CMOS low lux | **H.264** /MJPEG | **20x** Zoom | **IR** Distance 120 m. | **IP66**

Specification

Model	N-IP7235
Image Sensor	2.0M pixel CMOS low lux
Effective Pixels	2.0MP/1080P: 1920*1080
Min Lux	0.01Lux/F1.6, 0Lux(IR on)
S/N	>50db
Focus mode	Auto/manual
Optical zoom and focal length	20x zoom; F=4.7mm~84.6mm
Aperture	F1.6(Wide), F2.8(Far); auto Iris
IR distance	120M, 10pcs of imported LED
IR LED control	Auto/Near/Far/Shut
Horizontal Rotation Range	360°
Horizontal Rotation Speed	180°/s
Tilt Rotation Range	90°/180°
Tilt Rotation Speed	80°/s
Tours	8groups
Preset	128
Privacy mask	8
Bound rate	2400/4800/9600/19200
Network Interface	RJ45-10/100BASE-TX Fast Ethernet
Time Delay	0.16s
Video Frame	50Hz: 25fps (1280x960/432x240)
	60Hz: 30fps (1280x960/432x240)
Video Compression	H.264
Network Protocol	TCP/IP,HTTP,DDNS,DHCP,NTP,PPPoE,FTP,SMTP,RTSP,RTP
Network port	RJ45
Bit Rate	500kbps~6Mbps
Power Supply	DC12V 4A
Consumption	Max 48W
Protection Grade	IP66, Anti-lightening 4000V, anti-surge
Operating Temperature	-40~60ºC
Operating humidity	10~85%

RoHs CE FC