

SN-NVR10/02E3/016NSE


16CH 2HDD Network Video Recorder



Key features

- Up to 16ch 1080P IP cameras access
- Embedded Linux Operation System
- Support H.264 Video Compression
- 2 SATA hard disk up to 4TB (Max 8TB)
- 2RJ45 10M/100M/1000M network interface
- Simultaneous HDMI&VGA up to 1080P output
- 2 x 2.0 USB Host
- 2ch Alarm I/O
- Email push notification alert

Dimension



Interface Introduction

1. RJ45 10M/100M/1000M Network interface
2. RJ45 10M/100M/1000M Network interface
3. Reset
4. Audio I/O
5. VGA output
6. HDMI output
7. Alarm I/O
8. DC Power Supply

Specifications

VIDEO/AUDIO INPUT	
Video Input	16ch 6MP/5MP/4MP/3MP/1080P/960P/720P/D1/VGA/CIF/QCIF
Incoming Bandwidth	160Mbps ,(main stream 128Mbps ,sub stream 32Mbps)
Outgoing Bandwidth	128Mbps, Remote Live-view & Playback
Audio Input	1ch, G711_A/G711_U (Audio Compression)
VIDEO/AUDIO OUTPUT	
Recording Resolution	6MP/5MP/4MP/3MP/1080P/960P/720P/D1/VGA/CIF/QCIF
Frame Rate	6MP/5MP/4MP/3MP@15fps; 1080P@25fps(PAL),30fps(NTSC);
Live View/Playback Resolution	6MP/5MP/4MP/3MP/1080P/960P/720P/D1/VGA/CIF/QCIF
Live View/Playback Capacity	Live View 16ch D1/4ch 1080P,1ch 6MP/5MP/4MP/3MP Playback4ch 1080P/1ch 6MP/5MP/4MP/3MP
HDMI/VGA Output	1920x1080/60Hz,1280x720/60Hz,1024x768/60Hz
Audio Output	1ch,Line out
HARD DISK	
SATA HDD	2 SATA interface for 2HDD
Mounting Mode	Embedded
Capacity	Up to 4TB for each disk (Max 8TB)
NETWORK	
Network Interface	2 RJ45 10M/100M/1000M network interface
Protocol	IPv4, IPv6, TCP/IP, HTTP, SMTP, DHCP, DNS, NTP, SNMP, RTSP
POE Interface	N/A
System Compatibility	Onvif, SDK
INTERFACE	
HDMI/VGA	1ch HDMI, 1ch VGA
USB	USB 2.0 x2
Audio I/O	1ch MIC in,1ch audio line out
Alarm I/O	2ch Alarm output, 2ch Alarm input
Reset Button	Yes
GENERAL	
Power Supply	DC 12V,Max Input 36W
Power Consumption	Max 10W(without HDD,USB)
Operating Temperature	-10℃ ~+50℃
Operating Humidity	0% - 90% RH
Chassis	Mini 1U
Product Dimensions	372x311x44.5mm
Product Weight	<2.3kg