ASCCTV

คุณภาพคุ้มค่า ตอบทุกความต้องการ

KIT-08K - 2 MP
1080P Wireless IP camera

8 CH

1080P

Len
4/6 mm

18
IR Array

IP66

2.0MP/1080P Wireless IP camera

* Built-in WIFI module with high-performance and high stability
* Metal Bullet IP66 housing
* 18pcs Array, IR Distance: 20-25M
* 4/6mm 3.0MP HD Fixed lens
* 9pcs 12V2A Adaptor, 1pcs Cat5e cable

iOS ANDROID

1080P Wireless Network Video Recorder

* Built-in WIFI module with high-performance and high stability
* Automatically Connection between NVR and IPC
* Support video preview/recording/playback/backup
* Support the mixed use of wireless and wire,support different scene
* Support Android/IOS/PC remote

RoHS CE FC

ASCCTV

คุณภาพคุ้มค่า ตอบทุกความต้องการ

KIT-08K - 2 MP 1080P Wireless IP camera

Model	N-N408K (NVR)
Video input	8ch D1/960H720P/960P/1080P
HDMI Output	1ch，Resolution：1024x768, 1280x1024,1366x768,1400x900, 1920x1080
VGA Output	1ch，Resolution：1024x768, 1280x1024,1366x768,1400x900, 1920x1080
Resolution	D1/960H/720P/960P/1080P
Playback	4ch
Recording	Manual,time,motion detection,alarm
Storage	1 SATA
Storage capacity	6TB for each HDD
Network interface	1 RJ45 10M/100M，2 WIFI connector
USB interface	1 USB2.0
Audio interface	3.5 mm headphone jack（Optional）
Power consumption	≤5W
Power	DC12V
working temperature	-10℃--＋55℃
Dimension（mm）	258*210*42mm
Working humidity	10％--90％RH

WIFI Camera Specifications

Technical Parameters	Model	**N-IP5203WK (Camera)**
	Sensor	1/3” Progressive Scan Sensor
	Signal System	PAL/NTSC
	Resolution	1920 x 1080 16 : 9 High Defination
	Minimum illumination	Color : 0.1 Lux; B/W : 0.01 Lux
	Shutter	1/25s to 1/25,000s
	Lens	4/6mm
	OSD	Date Time & Title
	White Balance	Auto
	Day&Night	IR cut filter with auto switch
	3D-DNR	Auto
	Mirror/Flip	On / Off
	smart stream	Dual-stream : 1920x1080@15fps 640x480@15fps
	S/N	> 39.1 Db
	Interface	RJ45 / WIFI 802.11b/g/n
General Specification	Anti-thunder Level	Standard IEC61000-4-5
	Working Temperature/Humidity	-10℃ to +50℃ / 30% to 80% RH
	Working Temperature/Humidity	-20℃ to +60℃ / 20% to 90% RH
	Power Input	DC12V-1A
	Power consumption	≤6W
	Size	66*180mm
	Weight	500g
	Level of Protection	IP66