

SN-NVR10/02E3/016NSHP8


16CH 2HDD NVR with 8CH POE



Key features

- Up to 16ch IP cameras access
- Easy to use Same Interface of GUI/WEB/Client
- 2 SATA hard disk up to 6TB
- 1RJ45 10M/100M/1000M network interface
- 8ch POE Ports
- Simultaneous HDMI&VGA, up to 4K output
- 2 x 2.0&1x3.0 USB Host
- 2ch Alarm I/O
- 1ch Audio I/O
- 1U

Dimension



Interface Introduction

1. POE Ports
2. RJ45 10M/100M/1000M Network interface
3. Reset
4. Audio I/O
5. eSATA output
6. VGA output
7. HDMI output
8. USB output
9. Alarm I/O
10. AC110/220V Power Supply

Specifications

VIDEO/AUDIO INPUT	
Video Input	16ch h.265/h.264 8MP/6MP/5MP/4MP/3MP/1080P/720P
Incoming Bandwidth	160Mbps ,(main stream 128Mbps ,sub stream 32Mbps)
Outgoing Bandwidth	Total 256Mbps
Audio Input	1ch,Line in
VIDEO/AUDIO OUTPUT	
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080P/720P/D1/VGA/CIF/QCIF
Frame Rate	8MP/6MP/5MP/4MP/3MP/1080P/720P@25fps(PAL),30fps(NTSC)
Live View/Playback Resolution	8MP/6MP/5MP/4MP/3MP/1080P/720P/D1/VGA/CIF/QCIF
Live View/Playback Capacity	Live View 16ch 1080P/8ch 4MP/4ch 8MP,Playback 4ch 8MP/6MP/5MP/4MP/3MP/1080P/720P
HDMI/VGA Output	HDMI 3840x2160/60Hz,1920x1080/60Hz,1280x720/60Hz,1024x768/60Hz VGA 1920x1080/60Hz,1280x720/60Hz,1024x768/60Hz
Audio Output	1ch,Line out
HARD DISK	
SATA HDD	2 HDD Slot; Up to 6TB for each disk
Mounting Mode	Embedded
Capacity	Up to 6TB for each disk
NETWORK	
Network Interface	1 RJ45 10M/100M/1000M
Protocol	RTP/RTCP,TCP/UDP,HTTP,DHCP,DNS,NTP
POE Interface	8ch 100Mbps,IEEE802.3af/802.3at
POE Max Power	120W
INTERFACE	
HDMI/VGA	1ch HDMI, 1ch VGA
USB	USB 2.0 x2,USB 3.0 x1
Audio I/O	1ch MIC in,1ch audio line out
Alarm I/O	2ch Alarm input ,2ch Alarm output
Reset Button	Yes
GENERAL	
Power Supply	AC110/220V
Operating Temperature	-10℃~+45℃
Operating Humidity	0% - 90% RH
Chassis	1U
Product Dimensions	372x311x44.5mm
Product Weight	2.6kg (No disk)